

HomeGuard®



HomeGuard® HOUSEWRAP

Protecting you from the harsh elements of Mother Nature, HomeGuard® housewrap excels in air and water resistance, moisture vapor permeability and durability. HomeGuard housewrap is an engineered, woven, polyolefin material designed for use as a secondary weather resistive barrier. The strong woven fabric ensures jobsite durability, even in the harshest conditions. HomeGuard's micro-perforations allow damaging moisture as a vapor to escape while shedding bulk water.



HomeGuard is designed to protect commercial and residential buildings from Mother Nature by excelling in four crucial areas:



Air Resistance - Protects the wall assembly from air infiltration to increase the comfort of the building by reducing drafts and increasing energy efficiency.



Moisture Vapor Permeability - Preserves the integrity of the wall assembly by allowing the moisture as vapor to escape to the outside.



Water Resistance - Protects the wall assembly against water intrusion that gets behind the exterior cladding.



Durability - Has the ability to withstand the elements of the weather and tough jobsite conditions.

Test	Method	Units	HomeGuard	Minimum Requirement
Tensile Strength				
Machine Direction	ASTM D 882	lbs.	52	20
Cross Direction	ASTM D 882	lbs.	30	20
Water Resistance	ASTM D 779	Minutes	24 Hrs Pass	10 Minutes
Water-vapor Transmission	ASTM E 96 [Avg. A+B]	Perms	12	5
Low Temperature Bend	AC38 Section 3.3.4	N/A	Pass	Pass
UV Exposure	AC38 Section 4.1.2	N/A	6 Months	120 Days

Build your business with Custom Imprinting on HomeGuard® Housewrap



- Imprint your company logo - only one pallet minimum
- Largest exposure area - 40" x 30"
- Many colors are available
- Short lead times - 3 to 4 weeks on initial order, 2 weeks on reorders
- Logo repeats every 48" in center lane
- Available on 9' and 10' wide material

15 YEAR LIMITED WARRANTY HomeGuard® Weather Barrier System

Combine **HomeGuard® Housewraps** with **HomeGuard RA-Plus Flashing** or **Arctic-Flash Synthetic**, **HomeGuard Flexible Butyl Flashing**, **HomeGuard MS-Polymer Sealant** and **HomeGuard Seam Tape** to create an energy efficient, complete weather barrier system backed by a 15-year limited warranty.

HomeGuard RA-Plus Flashing-Rubberized Asphaltic flashing with excellent adhesion to most surfaces. Suitable for windows, doors, vents and most thru wall openings. UV Resistant for 180 days. Made in the USA.

HomeGuard Arctic-Flash-Extreme performance synthetic flashing with advanced acrylic adhesive provides a wide install temperature range from -20° F to extreme heat. UV Resistant for 180 days. Made in the USA.

HomeGuard Flexible Butyl Flashing-High performance flexible butyl adhesive flashing for arched windows and doors, window sills and custom shaped penetrations. UV Resistant for 180 days. Made in the USA.

HomeGuard MS-Polymer Sealant-Advanced STP-E polymer chemistry provides a superior bond to most substrates. Use it to seal windows, doors, column joints, gutters, vents/ducts and most molding, trim and siding. Compatible with HomeGuard weather barrier products. Made in the USA.

HomeGuard Seam Tape-UV Protected facer material with aggressive acrylic adhesive designed for sealing the seams of HomeGuard Housewraps.

HomeGuard Housewrap Roll Sizes and Quantities

3' x 100' - 234 rolls	4.5' x 100' - 156 rolls
3' x 150' - 165 rolls	4.5' x 150' - 110 rolls
3' x 195' - 120 rolls	5' x 200' - 80 rolls
9' x 100' - 78 rolls	10' x 100' - 78 rolls
9' x 150' - 55 rolls	10' x 150' - 55 rolls



Intertek
CCRR-1092
CCMC 13424-R



5430 Shawland Road • Jacksonville, FL 32254
Office: 904.240.1382 • Fax: 866.337.4016

www.HomeGuardBuildingProducts.com

HomeGuard